




REACH & RoHS COMPLIANT




LEFT SIDE VIEW




TOP VIEW




FRONT VIEW




RIGHT SIDE VIEW



BACK VIEW



BOTTOM VIEW



RECOMMENDED PCB LAYOUT VIEWED FROM COMPONENT SIDE

**MATERIAL:**

HOUSING: LCP,UL94V-0,BLACK.  
 TERMINAL: PHOSPHOR BRONZE Ø=0.46MM, G/FU" GOLD PLATING.  
 SHIELD: C2680,T=0.20MM,20 MIN NICKEL PLATING ON ALL AREA.


**MACHANICAL:**

DURABILITY: 750 CYCLES MIN,12.5MM/MINUTE.  
 INSERTION FORCE: 2.2KG.F MAX.  
 RETENTION STRENGTH : 7.7KG.F BETWEEN JACK AND PLUG .  
 OPERATING TEMPERATURE: -40 °C~+85°C.  
 STORAGE TEMPERATURE: -40°C~+85°C.  
 ALL CRITICAL DIMENSIONS WITH ""\*

**ELECTRICAL:**

VOLTAGE: 125 VOLTS AC.  
 CURRENT RATING : 1.5AMP.  
 DIELECTRIC STRENGTH: 1000 VAC RMS 50HZ OR 60HZ,1 MIN.  
 INSULATION RESISTANCE: 500 MEGA OHMS MIN. INITIAL  
 AFTER 500V DC FOR 1 MINUTE.  
 CONTACT RESISTANCE: SINGLE TERMINAL 30 MILLIOHMS MAX.

INITIAL 50 MILLIOHMS MAX. AFTER DURABILITY TEST.



**VOOHU** 苏州沃虎电子科技有限公司  
 Su Zhou Voohu Electronic Tech.Co.Ltd

TITLE:  
 RJ45 1\*1 8P8C无灯无弹

SIZE  
 A4  
 UNITS  
 MM[INCH]

GENERAL TOLERANCES  
 UNLESS SPECIFIED

APPROVED BY:  
 Geoffrey.Song

PART NO.:  
 SYT60S1188GWA6DY1008 (弯脚)

SACLE  
 1:1  
 REV  
 A0

x±0.35 x°±3.0°  
 .x±0.30 .x°±2.0°

CHECKED BY:  
 Elvis.Song

TEL: +86 400 1048 018

WEB: WWW.WOHU-TEK.COM

REMARK:

SHEET  
 1/1



.xx±0.25 .xx°±1.5°  
 .xxx±0.10 .xxx°±1.0°

DESIGND BY:  
 Sunny.Xu