








- NOTE:
- MATERIAL:
1. CONTACT: PHOSPHOR BRONZE.
 2. CONNECTOR HOUSING: LCP UL 94V-0. COLOR: BLACK.
 3. MOULDED INSERT: HIGH TEMPERATURE PLASTIC UL 94V-0. COLOR:BLACK.
 4. CAGE: COPPER ALLOY.
 5. LIGHT PIPES: POLYCARBONATE. UL 94V-0. COLOR:CLEAR
 6. LIGHT PIPE HOUSING: PBT UL 94V-0 COLOR:BLACK.
 7. EMI CLIP: COPPER ALLOY.
- PLATED:
1. CONTACT MATING AREA : PLATING GOLD 0.76 MICROMETERS MINIMUM OVER 1.27 MICROMETERS MINIMUM NICKEL.
 2. CONTACT NEEDLE EYE: 1.27 MICROMETERS MINIMUM MATTE TIN OVER 1.27 MICROMETERS MINIMUM NICKEL.





RoHS Compliant

A	 苏州沃虎电子科技有限公司 Su Zhou Voohu Electronic Tech.Co.Ltd		TITLE: SFP28 2X8 CONNECTOR	SIZE A4	UNITS MM[INCH]	GENERAL TOLERANCES UNLESS SPECIFIED		APPROVED BY: Geoffrey.Song
			PART NO.: WHSFP32328F003	SACLE 1:1	REV A0	$x \pm 0.35$	$x^\circ \pm 3.0^\circ$	CHECKED BY:
	TEL: +86 400 1048 018 WEB: WWW.VOOHU.CN		REMARK: Gold Plating 30U" NI 50U"	SHEET 1/3		$.xx \pm 0.25$	$.xx^\circ \pm 1.5^\circ$	DESIGND BY:
						$.xxx \pm 0.10$	$.xxx^\circ \pm 1.0^\circ$	Sunny.Xu



BEZEL CUT-OUT CENTER SPACING DETAIL
BEZEL THICKNESS:0.8-2.6



DETAIL A
SCALE 2:1

RoHS Compliant



苏州沃虎电子科技有限公司
Su Zhou Voohu Electronic Tech.Co.Ltd

TEL: +86 400 1048 018

WEB: WWW.VOOHU.CN

TITLE:
SFP28 2X8 CONNECTOR

PART NO.:
WHSFP32328F003

REMARK:
Gold Plating 30U" NI 50U"


SIZE
A4

SACLE
1:1

SHEET
2/3

UNITS
MM[INCH]

REV
A0




GENERAL TOLERANCES
UNLESS SPECIFIED

x±0.35	x°±3.0°
.x±0.30	.x°±2.0°
.xx±0.25	.xx°±1.5°
.xxx±0.10	.xxx°±1.0°


APPROVED BY:
Geoffrey.Song

CHECKED BY:
Elvis.Song

DESIGND BY:
Sunny.Xu



RECOMMENDED PCB LAYOUT—COMPONENT SIDE
RECOMMENDED PCB THICKNESS—2.63mm



DETAIL D
SCALE 2.5:1

RoHS Compliant



苏州沃虎电子科技有限公司
Su Zhou Voohu Electronic Tech.Co.Ltd

TITLE:
SFP28 2X8 CONNECTOR

PART NO.:
WHSFP32328F003

REMARK:
Gold Plating 30U" NI 50U"


SIZE
A4

SACLE
1:1

SHEET
3/3

UNITS
MM[INCH]

REV
A0



GENERAL TOLERANCES
UNLESS SPECIFIED

$x \pm 0.35$	$x^\circ \pm 3.0^\circ$
$.x \pm 0.30$	$.x^\circ \pm 2.0^\circ$
$.xx \pm 0.25$	$.xx^\circ \pm 1.5^\circ$
$.xxx \pm 0.10$	$.xxx^\circ \pm 1.0^\circ$

APPROVED BY:
Geoffrey.Song

CHECKED BY:
Elvis.Song

DESIGND BY:
Sunny.Xu

TEL: +86 400 1048 018

WEB: WWW.VOOHU.CN