


REACH & RoHS
COMPLIANT


1 Features And Benefits

- Very low primary resistance.
- Sensed current up to 40 Amps.
- Small SMD package.
- Operating temperature range -40 °C to 125 °C.
- Switch-mode power supplies.
- Feedback control.
- Overload sensing.
- Load drop/shut down detection.
- RoHS Compliant

2 Electrical Specifications @ 25°C



3 Schematics



Part Number	Secondary Inductance (mH)	Current Rating (A)	Turns Ratio	DCR (mΩ)		Hipot (V _{AC})
				Max	Max	
				Primary	Secondary	
				1-2	5-4	
WHPT-EP100-016	1.7	40	1:50	0.5	1500	3750
WHPT-EP100-017	3.0	40	1:70	0.5	2100	3750
WHPT-EP100-018	7.0	40	1:100	0.5	3100	3750
WHPT-EP100-019	11.0	40	1:125	0.5	4000	3750
WHPT-EP100-021	25.0	40	1:180	0.5	9000	3750
WHPT-EP100-020	32.0	40	1:200	0.5	10400	3750

VOOHU 苏州沃虎电子科技有限公司
Su Zhou Voohu Electronic Tech.Co.Ltd

TEL: +86 400 1048 018

WEB: WWW.WOHU-TEK.COM

TITLE:
SMT Current Sense Transformers

PART NO.:
WHPT-EP100-020

REMARK:
50K---500 kHz Available


SIZE
A4

SACLE
1:1

SHEET
1/4

UNITS
MM[INCH]

REV
A0



GENERAL TOLERANCES
UNLESS SPECIFIED

x±0.35	x°±3.0°
.x±0.30	.x°±2.0°
.xx±0.25	.xx°±1.5°
.xxx±0.10	.xxx°±1.0°







APPROVED BY:
Geoffrey.Song

CHECKED BY:
Elvis.Song


DESIGND BY:
Sunny.Xu

REACH & RoHS
COMPLIANT

4 Dimensions (mm)& recommend layout



5 Recommended Reflow Profile



MSL:

Grade: 1 level. Floor life: 0.5 year Condition: $\leq 30^{\circ}\text{C}/60\%\text{RH}$.

Ramp up rate= $3^{\circ}\text{C}/\text{s}$ max Ramp down rate= $6^{\circ}\text{C}/\text{s}$ max

$T_L=217^{\circ}\text{C}$ $t_L=60\text{s}-150\text{s}$ $T_P=250\pm 3^{\circ}\text{C}$ Time within 5°C of actual Peak Temperature (t_P): $20\sim 40\text{s}$

$T_{S\min}=150^{\circ}\text{C}$ $T_{S\max}=200^{\circ}\text{C}$ $T_{S\min}$ to $T_{S\max}$: $60\text{s}-180\text{s}$, 25°C to peak Temperature: 8minutes max

VOOHU 苏州沃虎电子科技有限公司
Su Zhou Voohu Electronic Tech.Co.Ltd

TITLE:
SMT Current Sense Transformers

SIZE
A4

UNITS
MM[INCH]

GENERAL TOLERANCES
UNLESS SPECIFIED

APPROVED BY:
Geoffrey.Song

PART NO.:
WHPT-EP100-020

SACLE
1:1

REV
A0


$x\pm 0.35$
 $.x\pm 0.30$

$x^{\circ}\pm 3.0^{\circ}$
 $.x^{\circ}\pm 2.0^{\circ}$

CHECKED BY:
Elvis.Song

REMARK:
50K---500 kHz Available

SHEET
2/4



$.xx\pm 0.25$
 $.xxx\pm 0.10$

$.xx^{\circ}\pm 1.5^{\circ}$
 $.xxx^{\circ}\pm 1.0^{\circ}$


DESIGND BY:
Sunny.Xu

TEL: +86 400 1048 018


WEB: WWW.WOHU-TEK.COM

REACH & RoHS
COMPLIANT


6 Packaging specification




Two Reel



Two Inner Carton



Inner Carton



Export Carton

Package Quantity:
One Reel=200 Pcs
One Inner Carton=200*2=400 Pcs
One Export Carton=400*2=800 Pcs

TITLE: SMT Current Sense Transformers	SIZE A4	UNITS MM[INCH]	GENERAL TOLERANCES UNLESS SPECIFIED		APPROVED BY: Geoffrey.Song
					CHECKED BY: Elvis.Song
PART NO.: WHPT-EP100-020	SACLE 1:1	REV A0	x±0.35	x°±3.0°	DESIGND BY: Sunny.Xu
			.x±0.30	.x°±2.0°	
			.xx±0.25	.xx°±1.5°	
REMARK: 50K---500 kHz Available	SHEET 3/4		.xxx±0.10	.xxx°±1.0°	

VOOHU 苏州沃虎电子科技有限公司
Su Zhou Voohu Electronic Tech.Co.Ltd

TEL: +86 400 1048 018 WEB: WWW.WOHU-TEK.COM

1		2		3		4		5		6		7		8	
REACH & RoHS COMPLIANT															
7 Reliability test						REMINDERS									
NO.		Test Item		Standard Reference		Test Condition									
1		Low temperature test		GB/T 2423.1		Temperature: -40±2℃ Time: 168 hours Measurement at 24±4 hours after test conclusion."									
2		High temperature storage test		GB/T 2423.2		Temperature: 125±2℃ Time: 168 hours Measurement at 24±4 hours after test conclusion.									
3		Constant temperature and constant humidity test		GB/T 2423.3 (IEC 60068-2-78)		Temperature: 40±2℃ / humidity:93±2%RH Time: 168 hours Measurement at 24±4 hours after test conclusion.									
4		High temperature and high humidity test		GB/T 2423.50		Temperature: 85±2℃ / humidity:85±2%RH Time: 168 hours Measurement at 24±4 hours after test conclusion.									
5		Thermal shock test		GB/T 2423.22 (IEC 60068-2-14)		First -40±5℃ for 30±2 minutes, last 85℃ 30±2 minutes as 1 cycle. Total 10 cycles.									
6		Salt spray test		GB/T2423.17 (IEC 60068-2-11)		Concentration :(5±0.1) % PH : 6.5 ~ 7.2 Temperature: 35 ±2 ℃ Time: 24 hours									
7		Solder ability test		GB/T 2423.28 (IEC 60068-2-20)		Preheating: 150±5℃, 60 seconds Immerse the terminal in flux for 5 seconds.then dip the terminal into a soldering bath of 245±5℃ for 3±1 seconds.									
8		Drop test		GB/T 2423.8 (IEC 60068-2-32)		Floor should be hard,strong,concrete. Height:1m. Test 6 surfaces , 3 ridges and 1 corner of Test-box.									
9		Vibration test		GB/T 4857.7		Frequency: 10-55-10Hz Sweep time: 1Min. Displacement:0.75mm, X,Y,Z axis 30Min respectively									
10		Soldering resistance test		GB/T 2423.50		Preheating: 150±5℃, 60~120 seconds Immerse the terminal in flux for 5 seconds.then dip the terminal into a soldering bath of 260±5℃ for 10±1 seconds.									
VOOHU 苏州沃虎电子科技有限公司 Su Zhou Voohu Electronic Tech.Co.Ltd				TITLE: SMT Current Sense Transformers				SIZE A4	UNITS MM[INCH]	GENERAL TOLERANCES UNLESS SPECIFIED		APPROVED BY: Geoffrey.Song			
				PART NO.: WHPT-EP100-020				SACLE 1:1	REV A0	x±0.35	x°±3.0°	CHECKED BY: Elvis.Song			
										.xx±0.30	.x°±2.0°				
TEL: +86 400 1048 018		WEB: WWW.WOHU-TEK.COM		REMARK: 50K---500 kHz Available				SHEET 4/4		.xx±0.25	.xx°±1.5°	DESIGND BY: Sunny.Xu			
										.xxx±0.10	.xxx°±1.0°				
1		2		3		4		5		6		7		8	