

Specification for Approval

产品承认书

Customer:

Customer P/N:

VOOHU P/N:

WHS16037D0

Version No.:

V0.1

Description:

10/100 BASE-TX

Laser Marking

SUZHOU VOOHU Company Approval		Customer Approval (客户承认签章)
DRAWN	Geoffrey.Song	
CHECKED	Sunny.Xu	
APPROVED	Elvis. Song	
日期DATE:2025/5/23		日期DATE: 2025/5/23

Please Return One Copy to Us After Approved,TKs! (承认后请回寄一份,谢谢)


VOOHU 沃虎
选沃虎 · 真靠谱

苏州沃虎电子科技有限公司
SuZhou Voohu Electronic Tech.Co.,Ltd


地址：江苏省苏州市吴江区开平商务中心G栋13楼
ADD: Building A, Alpha Building, Wujiang District,
Suzhou City, Jiangsu Province

TEL: 400 1048 018 WEB: www.wohu-tek.com/
+86 13338655578 E-MAIL: wohu@wohu-tek.com

A. MECHANICAL(unit:mm)



B. Schematics




DESCRIPTION	PART NO.	REV:R0
10/100 BASE-TX	WSH16037D0	PAGE:1/3

C. ELECTRICAL SPECIFICATIONS @25°C

Unless Otherwise Specified, Testing is Performed at 25°C ± 5°C

1. OCL: 350uH Min @ 100 KHz, 0.1V with 8mA DC BIAS
2. Leakage Inductance: 0.5uH Max @ 100KHz, 0.1V
3. DCR: 1400mΩ Max
4. Turns Ratio: 1CT:1CT±5%
5. Insertion Loss: -1.1 dB Max @ 1-100 MHz
6. Return Loss: -18 dB Min @ 1-30 MHz
-14.4 dB Min @ 40 MHz
-13.1 dB Min @ 50 MHz
-12 dB Min @ 60-80 MHz
7. Cross Talk: -30 dB Min @ 1-100 MHz
8. Common Mode Rejection: -30 dB Min @ 1-100 MHz
9. Isolation Hipot: 2500VAC 1mA 5S
10. Operating temperature -40°C to +85°C
11. Storage temperature -40°C to +85°C

D. RECOMMEND REFLOW PROFILE CURVE



MSL:

Grade: 1 level. Floor life: 0.5 year Condition: $\leq 30^\circ\text{C}/60\%\text{RH}$.

Ramp up rate=3°C/s max Ramp down rate=6°C/s max

$T_L=217^\circ\text{C}$ $t_L=60\text{s}-150\text{s}$ $T_P=250\pm 3^\circ\text{C}$ Time within 5°C of actual Peak Temperature




(t_P): 20~40s

$T_{s\ min}=150^\circ\text{C}$ $T_{s\ max}=200^\circ\text{C}$ $T_{s\ min}$ to $T_{s\ max}$: 60s-180s, 25°C to peak Temperature:


8minutes max

DESCRIPTION	PART NO.	REV:RO
10/100 BASE-TX	WHS16037D0	PAGE:2/3


E. Packaging specification




Three Reel



Inner Carton



Two Inner Carton



Export Carton

Package Quantity:

One Reel=600Pcs

One Inner Carton=600*3=1800Pcs

One Export Carton=1800*2=3600Pcs

DESCRIPTION	PART NO.	REV:R0
10/100 BASE-TX	WHS16037D0	PAGE: 3/3