

Specification for Approval

产品承认书

Customer:

Customer P/N:

VOOHU P/N:

WHSM24702N0

Version No.:

V0.1

Description:

10G BASE-T

Laser Marking

SUZHOU VOOHU Company Approval		Customer Approval (客户承认签章)
DRAWN	Geoffrey.Song	
CHECKED	Sunny.Xu	
APPROVED	Elvis. Song	
日期DATE:2025/11/24		日期DATE: 2025/11/24

Please Return One Copy to Us After Approved,TKs! (承认后请回寄一份,谢谢)

VOOHU 沃虎
造沃虎·真靠谱

苏州沃虎电子科技有限公司
SuZhou Voohu Electronic Tech.Co.,Ltd

地址：江苏省苏州市吴江区开平商务中心G栋13楼
ADD: Building A, Alpha Building, Wujiang District,
Suzhou City, Jiangsu Province



TEL: 400 1048 018
+86 13338655578

WEB: www.voohu.cn
E-MAIL: wohu@wohu-tek.com


[illegible]

DESCRIPTION	PART NO.	REV:R0
10G BASE-T	WHSM24702N0	PAGE:1/4

A. MECHANICAL(unit:mm)



B. Schematics




DESCRIPTION	PART NO.	REV:R0
10G BASE-T	WHSM24702N0	PAGE:2/4

C. ELECTRICAL SPECIFICATIONS @25°C

Unless Otherwise Specified, Testing is Performed at 25°C ± 5°C

1. OCL: 120 uH Min @100KHz 0.1V
2. Leakage Inductance: 0.5uH Max @ 100KHz, 0.1V
3. DCR: 900mΩ Max
4. Turns Ratio: 1CT:1CT±5%
5. Insertion Loss: -1.2dB max @ 1~200 MHz
-1.5dB max @ 200~300 MHz
-2.0dB max @ 300~400 MHz
-3.0dB max @ 400~500 MHz
6. Return Loss: -18 dB Min @ 1~100 MHz
-16 dB Min @ 100~200 MHz
-12 dB Min @ 200~300 MHz
-10 dB Min @ 300~400 MHz
-8 dB Min @ 400~500 MHz
7. Cross Talk: -25 dB Typ @ 1-500 MHz
8. Common Mode Rejection: -25 dB Typ @ 1-500 MHz
9. Isolation Hipot: 1500VAC 1mA 60S
10. Operating temperature 0°C to +70°C
11. Storage temperature -40°C to +85°C

D. RECOMMEND REFLOW SOLDERING CURVE



MSL:

Grade: 1 level. Floor life: 0.5 year Condition: ≤30°C/60%RH.




Ramp up rate=3°C/s max Ramp down rate=6°C/s max

TL=217°C tL=60s-150s Tp=250+/-3°C Time within 5°C of actual Peak Temperature (tp): 20~40s


Ts min=150°C Ts max=200°C Ts min to Ts max: 60s-180s, 25°C to peak Temperature: 8minutes max

DESCRIPTION	PART NO.	REV:R0
10G BASE-T	WHSM24702N0	PAGE:3/4


E. Packaging specification




Two Reel



Inner Carton



Five Inner Carton



Export Carton

Package Quantity:
 One Reel=350Pcs
 One Inner Carton=350*2=700Pcs
 One Export Carton=700*5=3500Pcs

DESCRIPTION	PART NO.	REV:R0
10G BASE-T	WHSM24702N0	PAGE:4/4