

Specification for Approval

产品承认书

Customer:

Customer P/N:

VOOHU P/N:

WHS24701D1

Version No.:

V0.1

Description:

100/1000 BASE-T

Laser Marking

SUZHOU VOOHU Company Approval		Customer Approval (客户承认签章)
DRAWN	Geoffrey.Song	
CHECKED	Sunny.Xu	
APPROVED	Elvis. Song	
日期DATE:2025/12/11		日期DATE: 2025/12/11

Please Return One Copy to Us After Approved,TKs! (承认后请回寄一份,谢谢)

VOOHU 沃虎
造沃虎·真靠谱

苏州沃虎电子科技有限公司
SuZhou Voohu Electronic Tech.Co.,Ltd

地址：江苏省苏州市吴江区开平商务中心G栋13楼
ADD: Building A, Alpha Building, Wujiang District,
Suzhou City, Jiangsu Province

TEL: 400 1048 018

WEB: www.voohu.cn


+86 13338655578

E-MAIL: wohu@wohu-tek.com


[illegible]

DESCRIPTION	PART NO.	REV:R0
100/1000 BASE-T	WHS G24701D1	PAGE:1/4

A. MECHANICAL(unit:mm)



B. SCHEMATICS




DESCRIPTION	PART NO.	REV:R0
100/1000 BASE-T	WHSG24701D1	PAGE:2/4

C. ELECTRICAL SPECIFICATIONS @25°C

Unless Otherwise Specified, Testing is Performed at 25°C ± 5°C

1. OCL: 350uH Min @ 100 KHz, 0.1V 8mA DC BIAS
2. Leakage Inductance: 0.5uH Max @ 100KHz, 0.1V
3. DCR: 1400mΩ Max
4. Turns Ratio: 1CT:1CT±5%
5. Insertion Loss: -1.1 dB Max @ 1-100 MHz
6. Return Loss: -18 dB Min @ 1-30 MHz
 - 14.4 dB Min @ 40 MHz
 - 13.1 dB Min @ 50 MHz
 - 12 dB Min @ 60-80 MHz
 - 10 dB Min @ 100MHz
7. Cross Talk: -30 dB Min @ 1-100 MHz
8. Common Mode Rejection: -30 dB Min @ 1-100 MHz
9. Isolation Hipot: 5000VAC 1mA 2S
10. Operating temperature -40°C to +85°C
11. Storage temperature -40°C to +85°C
12. PoE Support IEEE802.3af 15W: Each channel support 350mA DC balance current

D. RECOMMEND REFLOW SOLDERING CURVE



MSL:

Grade: 1 level. Floor life: 0.5 year Condition: ≤30°C/60%RH.


Ramp up rate=3°C/s max Ramp down rate=6°C/s max

TL=217°C tL=60s-150s Tp=250+/-3°C Time within 5°C of actual Peak Temperature (tp): 20~40s

Ts min=150°C Ts max=200°C Ts min to Ts max: 60s-180s, 25°C to peak Temperature: 8minutes max

DESCRIPTION	PART NO.	REV:R0
100/1000 BASE-T	WHS24701D1	PAGE:3/4

E. PACKAGE INFORMATION



Package Quantity:
 One Reel=350Pcs
 One Inner Carton=350*2=700Pcs
 One Export Carton=700*5=3500Pcs

DESCRIPTION	PART NO.	REV:R0
100/1000 BASE-T	WHS24701D1	PAGE:4/4